




Combo Tridem Chassis 20'-40', Spring-ride



SPECIFICATIONS

Overall Length	41' extended (carries one loaded 20' or 40' or two empty 20' ISO containers)
Overall Width	96"
Deck Height	48" (rear)
Coupler Height	46.5"
Kingpin Setting	17.5"
Weight	10,400 lbs. +/- 3%
GVWR	40' is 83,000 lbs.; 20' is 76,000 lbs.
Suspension	Tridem axle, 2-position, sliding spring-ride suspension
Axles	1/2" axle wall, 22,500 lb. capacity with synthetic wheel-end lubricant
Tires	255/70R22.5 radial tires for tridem axle application
Wheels	8.25 x 22.5 hub-piloted wheels
Brakes	16-1/2" x 7" x 3/4" s-cam, quick-change extended life brake shoes
ABS	4 sensor / 2 modulator-valve system
Upper Coupler	AAR certified coupler with 1/4" pick-up plate. Interior coupler surfaces sealed with corrosion resistant coating
Main Frame	One piece, high strength steel I-beams
Crossmembers	3/16" fabricated Z-sections
Bolsters	Heavy-duty with retractable front and rear twist locks, swing down center locks
Twist Locks	(12) Cast steel design to meet ISO standards and requirements
Landing Gear	AAR certified, self-lubricating 2-speed landing gear with internal gearbox and low-profile sand shoes
Lights & Wiring	LED lights with a fully sealed wiring harness and internal ground
Electrical Connections	7-way ATA plug with no circuit breakers
Air Connections	Fixed gladhands

Trailer specification features may vary based upon manufacturer model year, trailer type and location. Equipment is subject to availability at each location.