

40-Ton Double-drop Lowboy

50', Air-ride, Hydraulic Removable Gooseneck



FEATURES AND BENEFITS

• Adjustable Gooseneck Heights

All XTRA Lease trailers are spec'd to resist damage, ease loading and reduce maintenance costs. Here are just a few of the top features and benefits for this spec.

Loader Friendly

Extended Maintenance

- Extended Life Brake Linings
- Outriggers and Lashing Rings for
 - Cargo Control
- Synthetic Grease Wheel Ends
- Self-Lubricating Landing Gear

SPECIFICATIONS

| Deck Length 29' center deck (clear) Coupler Height 50" Kingpin Setting 15" Weight 17,845 lbs. +/- 3% Suspension Air-ride suspension, including automatic and manual raising an lowering system. Axles Two heavy-duty axles with 54.5" spread; 5/8" axle wall, 25,000 capacity with synthetic wheel-end lubricant. Tires 255/70R 22.5 premium radial tires Wheels 8.25" x 22.5" steel hub-piloted wheels Brakes 16-1/2" x 7" x 7/8" s-cam, quick-change extended- life brake sh ABS 4 sensor / 2 modulator-valve system Hydraulic removable gooseneck. Adjustable ride height feature position mechanical lock for separate deck and fifth wheel heig control. Self-contained hydraulic wet line system powered by 13 engine. Main Frame Fabricated high-tensile steel main beams Side Rails 12" steel I-beams Crasemembers 8" steel I-beam crossmembers on approx 23.5" centers on load | | |
|--|-----------------|---|
| Deck Height 18" main deck (loaded), 40" rear deck (6" ground clearance loa Deck Length 29' center deck (clear) Coupler Height 50" Kingpin Setting 15" Weight 17,845 lbs. +/- 3% Suspension Air-ride suspension, including automatic and manual raising an lowering system. Axles Two heavy-duty axles with 54.5" spread; 5/8" axle wall, 25,000 capacity with synthetic wheel-end lubricant. Tires 255/70R 22.5 premium radial tires Wheels 8.25" x 22.5" steel hub-piloted wheels Brakes 16-1/2" x 7" x 7/8" s-cam, quick-change extended- life brake sh ABS 4 sensor / 2 modulator-valve system Hydraulic removable gooseneck. Adjustable ride height feature position mechanical lock for separate deck and fifth wheel heig control. Self-contained hydraulic wet line system powered by 1: engine. Main Frame Fabricated high-tensile steel main beams Side Rails 12" steel I-beams 6" steel I-beams 8" steel I-beams | Overall Length | 50', 1" |
| Deck Length 29' center deck (clear) Coupler Height 50" Kingpin Setting 15" Weight 17,845 lbs. +/- 3% Suspension Air-ride suspension, including automatic and manual raising an lowering system. Axles Two heavy-duty axles with 54.5" spread; 5/8" axle wall, 25,000 capacity with synthetic wheel-end lubricant. Tires 255/70R 22.5 premium radial tires Wheels 8.25" x 22.5" steel hub-piloted wheels Brakes 16-1/2" x 7" x 7/8" s-cam, quick-change extended- life brake sh ABS 4 sensor / 2 modulator-valve system Hydraulic removable gooseneck. Adjustable ride height feature position mechanical lock for separate deck and fifth wheel heig control. Self-contained hydraulic wet line system powered by 13 engine. Main Frame Fabricated high-tensile steel main beams Side Rails 12" steel I-beams 8" steel I-beam crossmembers on approx 23.5" centers on load | Overall Width | 102" |
| Coupler Height 50" Kingpin Setting 15" Weight 17,845 lbs. +/- 3% Suspension Air-ride suspension, including automatic and manual raising an lowering system. Axles Two heavy-duty axles with 54.5" spread; 5/8" axle wall, 25,000 capacity with synthetic wheel-end lubricant. Tires 255/70R 22.5 premium radial tires Wheels 8.25" x 22.5" steel hub-piloted wheels Brakes 16-1/2" x 7" x 7/8" s-cam, quick-change extended- life brake sh ABS 4 sensor / 2 modulator-valve system Hydraulic removable gooseneck. Adjustable ride height feature position mechanical lock for separate deck and fifth wheel heig control. Self-contained hydraulic wet line system powered by 13 engine. Main Frame Fabricated high-tensile steel main beams Side Rails 12" steel I-beams 8" steel I-beam crossmembers on approx 23.5" centers on load | Deck Height | 18" main deck (loaded), 40" rear deck (6" ground clearance loaded) |
| Kingpin Setting 15" Weight 17,845 lbs. +/- 3% Suspension Air-ride suspension, including automatic and manual raising an lowering system. Axles Two heavy-duty axles with 54.5" spread; 5/8" axle wall, 25,000 capacity with synthetic wheel-end lubricant. Tires 255/70R 22.5 premium radial tires Wheels 8.25" x 22.5" steel hub-piloted wheels Brakes 16-1/2" x 7" x 7/8" s-cam, quick-change extended- life brake sh ABS 4 sensor / 2 modulator-valve system Hydraulic removable gooseneck. Adjustable ride height feature position mechanical lock for separate deck and fifth wheel heig control. Self-contained hydraulic wet line system powered by 11 engine. Main Frame Fabricated high-tensile steel main beams Side Rails 12" steel I-beams 8" steel I-beam crossmembers on approx 23.5" centers on load | Deck Length | 29' center deck (clear) |
| Weight 17,845 lbs. +/- 3% Suspension Air-ride suspension, including automatic and manual raising an lowering system. Axles Two heavy-duty axles with 54.5" spread; 5/8" axle wall, 25,000 capacity with synthetic wheel-end lubricant. Tires 255/70R 22.5 premium radial tires Wheels 8.25" x 22.5" steel hub-piloted wheels Brakes 16-1/2" x 7" x 7/8" s-cam, quick-change extended- life brake sh ABS 4 sensor / 2 modulator-valve system Hydraulic removable gooseneck. Adjustable ride height feature position mechanical lock for separate deck and fifth wheel heig control. Self-contained hydraulic wet line system powered by 1: engine. Main Frame Fabricated high-tensile steel main beams Side Rails 12" steel I-beams 8" steel I-beam crossmembers on approx 23.5" centers on load | Coupler Height | 50" |
| Air-ride suspension, including automatic and manual raising an lowering system. Axles Two heavy-duty axles with 54.5" spread; 5/8" axle wall, 25,000 capacity with synthetic wheel-end lubricant. Tires 255/70R 22.5 premium radial tires Wheels 8.25" x 22.5" steel hub-piloted wheels Brakes 16-1/2" x 7" x 7/8" s-cam, quick-change extended- life brake sh ABS 4 sensor / 2 modulator-valve system Hydraulic removable gooseneck. Adjustable ride height feature position mechanical lock for separate deck and fifth wheel heig control. Self-contained hydraulic wet line system powered by 13 engine. Main Frame Fabricated high-tensile steel main beams Side Rails 12" steel I-beams 8" steel I-beam crossmembers on approx 23.5" centers on load | Kingpin Setting | 15" |
| Suspension lowering system. Axles Two heavy-duty axles with 54.5" spread; 5/8" axle wall, 25,000 capacity with synthetic wheel-end lubricant. Tires 255/70R 22.5 premium radial tires Wheels 8.25" x 22.5" steel hub-piloted wheels Brakes 16-1/2" x 7" x 7/8" s-cam, quick-change extended- life brake sh ABS 4 sensor / 2 modulator-valve system Hydraulic removable gooseneck. Adjustable ride height feature position mechanical lock for separate deck and fifth wheel heig control. Self-contained hydraulic wet line system powered by 1: engine. Main Frame Fabricated high-tensile steel main beams Side Rails 12" steel I-beams 8" steel I-beam crossmembers on approx 23.5" centers on load | Weight | 17,845 lbs. +/- 3% |
| Axies capacity with synthetic wheel-end lubricant. Tires 255/70R 22.5 premium radial tires Wheels 8.25" x 22.5" steel hub-piloted wheels Brakes 16-1/2" x 7" x 7/8" s-cam, quick-change extended- life brake sh ABS 4 sensor / 2 modulator-valve system Hydraulic removable gooseneck. Adjustable ride height feature position mechanical lock for separate deck and fifth wheel heig control. Self-contained hydraulic wet line system powered by 13 engine. Main Frame Fabricated high-tensile steel main beams Side Rails 12" steel I-beams 8" steel I-beam crossmembers on approx 23.5" centers on load | Suspension | Air-ride suspension, including automatic and manual raising and lowering system. |
| Wheels 8.25" x 22.5" steel hub-piloted wheels Brakes 16-1/2" x 7" x 7/8" s-cam, quick-change extended- life brake sh ABS 4 sensor / 2 modulator-valve system Gooseneck Hydraulic removable gooseneck. Adjustable ride height feature position mechanical lock for separate deck and fifth wheel heig control. Self-contained hydraulic wet line system powered by 1: engine. Main Frame Fabricated high-tensile steel main beams Side Rails 12" steel I-beams 8" steel I-beam crossmembers on approx 23.5" centers on loar | Axles | Two heavy-duty axles with 54.5" spread; 5/8" axle wall, 25,000 lb. capacity with synthetic wheel-end lubricant. |
| Brakes 16-1/2" x 7" x 7/8" s-cam, quick-change extended- life brake sh ABS 4 sensor / 2 modulator-valve system Hydraulic removable gooseneck. Adjustable ride height feature position mechanical lock for separate deck and fifth wheel heig control. Self-contained hydraulic wet line system powered by 13 engine. Main Frame Fabricated high-tensile steel main beams Side Rails 12" steel I-beams 8" steel I-beam crossmembers on approx 23.5" centers on load | Tires | 255/70R 22.5 premium radial tires |
| ABS 4 sensor / 2 modulator-valve system Gooseneck Hydraulic removable gooseneck. Adjustable ride height feature position mechanical lock for separate deck and fifth wheel heig control. Self-contained hydraulic wet line system powered by 13 engine. Main Frame Fabricated high-tensile steel main beams Side Rails 12" steel I-beams 8" steel I-beam crossmembers on approx 23.5" centers on load | Wheels | 8.25" x 22.5" steel hub-piloted wheels |
| Gooseneck Hydraulic removable gooseneck. Adjustable ride height feature position mechanical lock for separate deck and fifth wheel heig control. Self-contained hydraulic wet line system powered by 13 engine. Main Frame Fabricated high-tensile steel main beams Side Rails 12" steel I-beams 8" steel I-beam crossmembers on approx 23.5" centers on load | Brakes | 16-1/2" x 7" x 7/8" s-cam, quick-change extended- life brake shoes |
| Gooseneck position mechanical lock for separate deck and fifth wheel heig control. Self-contained hydraulic wet line system powered by 13 engine. Main Frame Fabricated high-tensile steel main beams Side Rails 12" steel I-beams 8" steel I-beam crossmembers on approx 23.5" centers on load | ABS | 4 sensor / 2 modulator-valve system |
| Side Rails 12" steel I-beams 8" steel I-beam crossmembers on approx 23.5" centers on loa | Gooseneck | Hydraulic removable gooseneck. Adjustable ride height features five- position mechanical lock for separate deck and fifth wheel height control. Self-contained hydraulic wet line system powered by 13HP gas engine. |
| 8" steel I-beam crossmembers on approx 23.5" centers on loa | Main Frame | Fabricated high-tensile steel main beams |
| | Side Rails | 12" steel I-beams |
| - steel -beam on to centers on upper and real deck. | Crossmembers | 8" steel I-beam crossmembers on approx 23.5" centers on load deck; 4" steel I-beam on 18' centers on upper and rear deck. |



SPECIFICATIONS

| Bolsters | Heavy-duty bolsters with chain slots and flag holders behind each axle |
|------------------------|---|
| Cargo Control | 7 lash ring pairs & 14 outrigger pairs |
| Floor | 1-3/8" apitong center deck; 1-1/8" apitong front and rear covered deck. Sloped steel front bogie ramp, full width. |
| Lights & Wiring | Sealed-beam lights with a fully sealed wiring harness and internal ground |
| Electrical Connections | 7-way ATA plug with no circuit breakers |

Trailer specification features may vary based upon manufacturer model year, trailer type and location. Equipment is subject to availability at each location.

