



# 40-Ton Double-drop Lowboy 47' 11", Air-ride, Mechanical Removable Gooseneck



## FEATURES AND BENEFITS

All XTRA Lease trailers are spec'd to resist damage, ease loading and reduce maintenance costs. Here are just a few of the top features and benefits for this spec.

### Loader Friendly

- Adjustable Gooseneck Heights
- Outriggers and Lashing Rings for Cargo Control

### Extended Maintenance

- Extended Life Brake Linings
- Synthetic Grease Wheel Ends
- Self-Lubricating Landing Gear

## SPECIFICATIONS

<b>Overall Length</b>	47', 11"
<b>Overall Width</b>	102"
<b>Deck Height</b>	18" main deck (loaded), 40" rear deck (6" ground clearance loaded)
<b>Deck Length</b>	29' center deck (clear); 9'-2" rear deck length
<b>Gooseneck Length</b>	9'-10"
<b>Coupler Height</b>	50 – 52"
<b>Kingpin Setting</b>	16"
<b>Weight</b>	16,140 lbs. +/- 3%
<b>Suspension</b>	Air-ride suspension, including automatic and manual raising and lowering system.
<b>Axles</b>	Two heavy-duty axles with 54.5" spread; 5/8" axle wall, 25,000 lb. capacity with synthetic wheel-end lubricant.
<b>Tires</b>	255/70R 22.5 premium radial tires
<b>Wheels</b>	8.25" x 22.5" steel hub-piloted wheels
<b>Brakes</b>	16-1/2" x 7" x 7/8" s-cam, quick-change extended- life brake shoes
<b>ABS</b>	4 sensor / 2 modulator-valve system
<b>Gooseneck</b>	Full-width mechanical removable gooseneck with removable fifth wheel guide rollers. Combination figure-8 plate which provides 50 inches and 52 inches loaded. 81" swing radius. 16" king pin setting.
<b>Main Frame</b>	Fabricated high-tensile steel main beams
<b>Side Rails</b>	12" steel I-beams



# 40-Ton Double-drop Lowboy 47', 11", Air-ride, Hydraulic Removable Gooseneck

## SPECIFICATIONS

<b>Crossmembers</b>	8" steel I-beam crossmembers on approx. 24" centers on load deck; 4" steel I-beam on 16.5" centers on front and 14" on rear deck.
<b>Bolsters</b>	Heavy-duty bolsters with chain slots and flag holders behind each axle
<b>Cargo Control</b>	9 lash ring pairs & 14 outrigger pairs
<b>Floor</b>	1-3/8" apitong center deck; 1-1/8" apitong front and rear covered deck. Sloped steel front bogie ramp, full width.
<b>Lights &amp; Wiring</b>	Trucklite flange mounted LED package with anti-theft rings, #10-marker lights (7 per side), Super 44 -stop, tail and directional (2 per side)
<b>Electrical Connections</b>	7-way ATA plug with no circuit breakers

Trailer specification features may vary based upon manufacturer model year, trailer type and location. Equipment is subject to availability at each location.

