



# Double-Drop Extendable Flatbed 48', Air-ride

## FEATURES AND BENEFITS

All XTRA Lease trailers are spec'd to resist damage, ease loading and reduce maintenance costs. Here are just a few of the top features and benefits for this spec.

### Loader Friendly

- Lashing Rings For Cargo Control

### Extended Maintenance

- Extended Life Brake Linings
- Synthetic Grease Wheel Ends
- Self-Lubricating Landing Gear

### Damage Resistant

- Heavy Duty Main Beams And Side Rails

## SPECIFICATIONS

<b>Overall Length</b>	48' to 69' (Extends in 5' Increments)
<b>Overall Width</b>	102"
<b>Deck Height</b>	20" center deck, 41" rear deck
<b>Center Deck Length</b>	29' – 50'; stops on five 12-inch increments
<b>Coupler Height</b>	50"
<b>Kingpin Setting</b>	16"
<b>Weight</b>	20,100 lbs. +/- 3%
<b>Suspension</b>	Fixed position tandem axles with Air-Ride suspension. Airbags equipped with self-regulating height control valve and manual dump valve
<b>Axles</b>	5/8" axle wall, 25,000 lb. capacity with synthetic wheel-end lubricant
<b>Tires</b>	255/70R 22.5 premium radial tires
<b>Wheels</b>	8.25" x 22.5" steel hub-piloted wheels
<b>Brakes</b>	16-1/2" x 7" x 3/4" s-cam, quick-change, extended life brake shoes
<b>ABS</b>	2 sensor / 1 modulator-valve system
<b>Upper Coupler</b>	AAR certified coupler with 1/4" pick-up and 5th-wheel plates. Interior coupler surfaces sealed with corrosion resistant coating
<b>Main Frame</b>	Fabricated high-tensile steel main beams, air operated stops on 5' increments
<b>Side Rails</b>	6" structural steel channel on front deck, 8" on center deck
<b>Crossmembers</b>	4" steel crossmembers on 18" centers under front deck, 8" steel crossmembers on 24" centers on center deck
<b>Landing Gear</b>	AAR certified, self-lubricating 2-speed landing gear with internal gearbox and cushion sand shoes



## Double-Drop Extendable Flatbed 48', Air-ride

### SPECIFICATIONS

<b>Cargo Control</b>	Nine pair of lashing rings
<b>Floor</b>	1-1/8" apitong floor
<b>Bulkhead</b>	48" Flat, Removable Bulkhead
<b>Lights &amp; Wiring</b>	Sealed-beam lights with a fully sealed wiring harness and internal ground
<b>Electrical Connections</b>	7-way ATA plug with no circuit breakers
<b>Air Connections</b>	Stationary gladhands mounted on roadside

Trailer specification features may vary based upon manufacturer, model year, trailer type and location.  
Equipment is subject to availability at each location.